

BD 1100

Dual 4" 5-Element 3-Way Reference Floorstanding Tower



List Price: \$2,500 pr. (\$1,250 ea.)

SPECIAL FEATURES:

- ▶ Beautiful multi-layer piano lacquer finish, a process that takes 1 full week to produce each cabinet
- ▶ Butyl rubber surrounds provide excellent cone control & exceptional durability
- ▶ Solid brass isolation cones for optimal bass response
- ▶ Built-in automatic protection circuit prevents overload
- ▶ Metal grille fasteners to prevent breakage
- ▶ Gold plated binding posts for a high quality and secure connection
- ▶ New 12 Year Transferable Warranty on parts & labor
- ▶ Designed in the US A

Component Drivers:

- (1) 1" liquid cooled silk dome tweeter
- (2) 4" glass fibercone midranges with w/rubber surrounds
- (2) 4" glass fibercone woofers w/rubber surrounds

Frequency Range @ -6 dB: Low: 39 Hz, High: 30 kHz

Frequency Response: 49 Hz - 25 kHz (+/- 3 dB)

Crossover Frequency: 200 Hz & 5 kHz

Recommended Amplifier Power: 15 - 200 Watts RMS per channel

Operative Power Range: 15 - 150 Watts, 300 Watts Peak

Sensitivity: 92 dB @ 1 Watt / 0.5 Meter (2.83 Volts Pink Noise)

Nominal Impedance: 8 Ohms

Dimensions: 6 13/16" W x 44 3/16" H x 12 1/2" D (w/grille & isolation cones)

