

BD 2000 SERIES II

Dual 6.5" 4-Element, 3-Way Reference Floorstanding Tower



List Price: \$7,000 pr. (\$3,500 ea.)

SPECIAL FEATURES

- ▶ Beautiful multi-layer piano lacquer finish, a process that takes 1 full week to produce each cabinet
- ▶ Dedicated midrange driver for superior clarity & detail
- ▶ Die cast metal woofer baskets for improved bass definition
- ▶ Die cast phase plug for improved crossover function
- ▶ Solid brass isolation cones for optimal bass response
- ▶ Butyl rubber surrounds provide excellent cone control & exceptional durability
- ▶ Built-in automatic protection circuit prevents overload
- ▶ Video shielded allows placement near TV without interference
- ▶ Gold plated binding posts for a high quality and secure connection
- ▶ Metal grille fasteners to prevent breakage
- ▶ New 12 Year Transferable Warranty on Parts & Labor
- ▶ Designed in the USA

Component Drivers:

1" liquid cooled silk dome tweeter with neodymium magnet

4" polypropylene midrange with butyl surround and die cast phase plug

(2) 6.5" polypropylene woofers with butyl surrounds and die cast baskets

Frequency Range @ -6 dB: Low: 29 Hz, High: 30 kHz

Frequency Response: 31 Hz - 25 kHz (+/- 3 dB)

Crossover Frequencies: 500 Hz & 4 kHz

Recommended Amplifier Power: 15 - 200 Watts RMS per channel

Operative Power Range: 15 - 200 Watts, 400 Watts Peak

Sensitivity: 94 dB @ 1 Watt / 0.5 Meter (2.83 Volts Pink Noise)

Nominal Impedance: 8 Ohms

Dimensions: 8 7/8" W x 39" H x 14 3/8" D (with grille)

