

BD 500 SERIES II

5.25" 2-Way Reference Monitors



List Price: \$650 pr.

SPECIAL FEATURES

- ▶ Beautiful multi-layer piano lacquer finish, a process that takes 1 full week to produce each cabinet
- ▶ Butyl rubber surround provides excellent cone control and exceptional durability
- ▶ 1/4-20 threaded insert allows for pivot bracket mounting
- ▶ Built-in automatic protection circuit prevents overload
- ▶ Video shielding allows placement near TV without interference
- ▶ Metal grille fasteners to prevent breakage
- ▶ Gold plated binding posts for a high quality and secure connection
- ▶ New 12 Year Transferable Warranty on parts & labor
- ▶ Designed in the USA

Component Drivers:

1" liquid cooled silk dome tweeter with neodymium magnet

5.25" polymer cone woofer w/rubber surround & die cast phase plug

Frequency Range @ -6 dB: Low: 45 Hz, High: 27 kHz

Frequency Response: 49 Hz - 23 kHz (+/- 3 dB)

Crossover Frequency: 5 kHz

Recommended Amplifier Power: 15 - 125 Watts RMS per channel

Sensitivity: 90 dB @ 1 Watt / 0.5 Meter (2.83 Volts Pink Noise)

Nominal Impedance: 8 Ohms

Dimensions: 6 3/8" W x 9 1/2" H x 8 1/8" D

