

BD 600 SERIES II

Dual 6.5" 4-Element, 3-Way, Full Range Reference Center Channel



List Price: \$1000 ea.

SPECIAL FEATURES:

- ▶ Beautiful multi-layer piano lacquer finish, a process that takes 1 full week to produce each cabinet
- ▶ Dedicated midrange driver for superior clarity & detail
- ▶ Die cast metal woofer basket for improved bass definition
- ▶ Die cast phase plug for improved crossover function
- ▶ Butyl rubber surround provides excellent cone control & exceptional durability
- ▶ Video shielding allows placement near TV without interference
- ▶ Metal grille fasteners to prevent breakage
- ▶ Built-in automatic protection circuit prevents overload
- ▶ Gold plated binding posts for a high quality and secure connection
- ▶ New 12 Year Transferable Warranty on parts & labor
- ▶ Designed in the USA

Component Drivers:

- (1) 1" liquid cooled silk dome tweeter with neodymium magnet
- (1) 4" polycone midrange with butyl surround and die cast phase plug
- (2) 6.5" polycone woofers with butyl surrounds and die cast baskets

Frequency Range @ -6 dB: Low: 30 Hz, High: 30 kHz

Frequency Response: 55 Hz - 25 kHz (+/- 3 dB)

Crossover Frequencies: 500 Hz & 4 kHz

Recommended Amplifier Power: 15 - 200 Watts RMS per channel

Operative Power Range: 15 - 200 Watts, 300 Watts Peak

Sensitivity: 90 dB @ 1 Watt / 0.5 Meter (2.83 Volts Pink Noise)

Nominal Impedance: 8 Ohms

Dimensions: 20 3/8" W x 8 7/8" H x 9 1/2" D (with grille)

