

BD 650 SERIES II

6.5" 3-Way, Full Range Reference Monitors



List Price: \$1,500 pr.

SPECIAL FEATURES

- ▶ Beautiful multi-layer piano lacquer finish, a process that takes 1 full week to produce each cabinet
- ▶ Dedicated midrange driver for superior clarity & detail
- ▶ Die cast metal woofer basket for improved bass definition
- ▶ Die cast phase plug for improved crossover function
- ▶ Butyl rubber surround provides excellent cone control & exceptional durability
- ▶ Built-in automatic protection circuit prevents overload
- ▶ Video shielding allows placement near TV without interference
- ▶ Gold plated binding posts for a high quality and secure connection
- ▶ Metal grille fasteners to prevent breakage
- ▶ New 12 Year Transferable Warranty on Parts & Labor
- ▶ Designed in the USA

Component Drivers:

1" liquid cooled silk dome tweeter with neodymium magnet

4" polypropylene midrange with butyl surround and die cast phase plug

6.5" polypropylene woofer with butyl surround and die cast basket

Frequency Range @ -6 dB: Low: 30 Hz, High: 30 kHz

Frequency Response: 34 Hz - 25 kHz (+/- 3 dB)

Crossover Frequencies: 500 Hz & 4 kHz

Recommended Amplifier Power: 15 - 200 Watts RMS per channel

Operative Power Range: 15 - 200 Watts, 300 Watts Peak

Sensitivity: 93 dB @ 1 Watt / 0.5 Meter (2.83 Volts Pink Noise)

Nominal Impedance: 8 Ohms

Dimensions: 8 3/4" W x 15 5/8" H x 14 1/8" D (with grille)

