

# K

SERIES

## K6 & K8



Our **Kevlar® Series** of custom in-wall and ceiling speakers are designed for superior sound backed by “bulletproof” durability. Kevlar®, a cutting edge polymer, is the material of choice for highly specialized applications where strength and reliability is critical. Its superior acoustical qualities, when molded into speaker cones, are further enhanced by our custom crafted crossover networks, known for their meticulous detail and component quality. The result is unparalleled sound and performance from this series of superb custom install speakers.

### Special Features

- Special Kevlar® cone for superior stability and detail at all power levels
- Custom crafted crossover networks reveal crisp, precise response
- Pivot-mount Titanium dome tweeter for the best performance and placement flexibility
- Automatic Overload Protection Circuit
- Hardware in place for easy wall mount installation
- LIFETIME transferable warranty on parts & labor
- Gold-plated binding posts
- Designed in the USA

### Specifications

#### K 6

#### K 8

Specifications	K 6	K 8
<b>System Type</b>	2-Way, Acoustic Suspension	2-Way, Acoustic Suspension
<b>Component Drivers</b>	¾" liquid cooled titanium pivoting tweeter	1" liquid cooled titanium pivoting tweeter
<b>Frequency Response</b>	6.5" Kevlar® cone woofer with butyl surround 60 - 20 kHz (+/- 3 dB)	8" Kevlar® cone woofer with butyl surround 50 - 20 kHz (+/- 3 dB)
<b>Crossover Frequency</b>	4 kHz	4 kHz
<b>Recommended Amplifier Power</b>	20 - 120 Watts RMS per channel	20 - 120 Watts RMS per channel
<b>Sensitivity</b>	87 dB @ 1 Watt/1 Meter (2.83 Volts Pink Noise)	87 dB @ 1 Watt/1 Meter (2.83 Volts Pink Noise)
<b>Nominal Impedance</b>	8 Ohms	8 Ohms
<b>Dimensions</b>	9" Round x 3" Deep (7 7/8" cutout)	10 3/4" Round x 3 3/4" Deep (9 5/8" cutout)
<b>Finish</b>	White	White
<b>Weight</b>	5 lbs. / pair	8 lbs. / pair