

WAFR-FLUSH CTR 525

5-Element Dual 5.25" 4-Way In-Wall Audiophile Center Speaker Channel



Our Wafer Series of custom In-Wall and In-Ceiling speakers are designed to deliver Pinnacle's superior performance without being seen. Our special low-profile grille design completely covers the speaker and protrudes from the wall a mere 4mm , four times less than standard designs!

Special Features

- No bezel, super flush design protrudes only 4mm from the ceiling. Four times less than standard designs!
- Specially mounted microperf grille completely covers the speakers trim lip for clean, sleek look
- Video shielded to allow placement near TV without interference
- Magnetic grille fastening system for easy install
- 12 3/4" width fits between studs
- Custom crafted crossover networks reveal crisp, precise response
- Special polymer woofer cones for superior stability and detail at all power levels
- Pivot-mount silk dome tweeter and supertweeter for the best performance and placement flexibility
- Built-in automatic protection circuit prevents overload
- Butyl rubber surrounds provide excellent cone control and exceptional durability
- Gold plated push-pin binding posts for quick, secure & high quality connection
- Hardware in place for easy ceiling mount installation
- Rough-in kit available separately
- Designed in the USA
- 10-year warranty

Specifications

Component Drivers: 1" liquid cooled pivoting silk dome supertweeter and tweeter with neodymium magnet; 3" polycone, high definition midrange with butyl rubber surround;

(2) 5.25" polycone, long throw woofers with butyl rubber surrounds, 18 ounce magnets & 1" voice coils

Frequency Response: 60 - 20 kHz (+/- 3 dB)

Recommended Amplifier Power: 20-200 Watts RMS per channel

Sensitivity: 86 dB @ 1 Watt / 1 Meter (2.83 Volts Pink Noise)

Nominal Impedance: 8 Ohms

Dimensions: 13 7/8" W x 9 7/8" H x 3 7/16" D (Cutout: 12 3/4"W x 8 3/4" H)

